



AP-11SK

Sensor Head, Negative-pressure Type, -100 kPa



*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

Specifications

Model		AP-11SK
Type		Negative Sensor Head
Rated pressure		-29.9 to 0 inchHg
Fluid type		Gases and liquids compatible with 304 and 630 stainless steel
Type of pressure		Gauge pressure
Repeatability		0.5 % of F.S. max.
Connection port		1/8 NPT
Environmental resistance	Enclosure rating	IP67
	Pressure resistance	72.5 PSI
	Ambient temperature	-10 to 70°C(14 to 158°F), No condensation
	Relative humidity	35 to 85%, No condensation
	Vibration resistance	10 to 55 Hz, 1.5 mm 0.06" double amplitude in X, Y, and Z directions, 3 hours respectively
	Shock resistance	500 m/s² in X, Y, and Z directions 10 times respectively (60 times in total)
Material		Diaphragm pressure port: TYPE S17400 stainless steel, Pressure port: 304 stainless steel, Throttle: 304 stainless steel (AP-14SK/15SK/16SK only)
Accessories		Sensor head connector: 1
Weight		Approx. 120 g

Dimensions

* Download CAD file or product manual for larger image/text and more detail.

