

Basic features

Approval/Conformity	CE UKCA cULus WEEE
Basic standard	IEC 60947-5-2 IEC 60947-5-7

Display/Operation

Function indicator	Adjustment indicator
Power indicator	no

Electrical connection

Connection	M12x1-Male, 4-pin, A-coded
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

Electrical data

Limit frequency –3 dB	1000 Hz
No-load current I _{o max.} at U _e	19 mA
Operating voltage U _b	18...30 VDC
Protection class	II
Rated insulation voltage U _i	250 V AC
Rated operating voltage U _{e DC}	24 V
Ripple max. (% of U _e)	15 %

Environmental conditions

Ambient temperature	-40...80 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 g _n , 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP67

Functional safety

MTTF (40 °C)	462 a
--------------	-------

IO-Link

IO-Link Profil IDs	N/A
--------------------	-----

Interface

Interface	IO-Link 1.1 12 bits
Output characteristic	falling on approach
Process data OUT	2 bytes

Material

Housing material	Brass, Nickel-free coated
Material sensing surface	LCP

Mechanical data

Dimension	∅ 12 x 65 mm
Installation	non-flush
Mounting length	43.9 mm
Size	M12x1
Tightening torque	10 Nm

Range/Distance

Linearity range SI	0.2...7 mm
Measuring range	0.2...7 mm

Non-linearity max.	±70 µm
Repeat accuracy per BWN	±14 µm
Temperature drift max. from end value	±5.0 %

Remarks

Values referenced to axial approach of St 37 target. For other materials correction factors are applied.

Scattering (e.g. due to manufacturing tolerances) is described by the tolerance T at Se. This can be approximated using the formula: $T = (sl_{max} + sl_{min}) / 20 = \pm xx \text{ mm}$.

UL-MARKINGS: - For use in NFPA 79 Applications only - Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.


For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.


Connector Drawings



Wiring Diagrams (Schematic)



Technical Drawings



Help Views

Octet 0								Octet 1									
7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0		
MSB								Position value				LSB	OoR	BDC3	BDC2	BDC1	