



1) Sensing surface, 2) Housing, 3) Cover, 4) Potentiometer, 5) LED function indicator



Basic features

Approval/Conformity	CE
	UKCA
	cULus
	WEEE
Basic standard	IEC 60947-5-2
Scope of delivery	Nut (2x)
	Screwdriver
	Short guide
Sensitivity	Switching distance adjustable
Series	M12

Electrical data

No-load current $I_0$ max. at $U_e$	15 mA
Operating voltage $U_b$	12...35 VDC
Rated insulation voltage $U_i$	75 V DC
Rated operating current $I_e$	200 mA
Rated operating voltage $U_e$ DC	24 V
Ripple max. (% of $U_e$ )	10 %
Switching frequency	25 Hz
Utilization category	DC -13
Voltage drop static max.	0.8 V

Display/Operation

Function indicator	yes
--------------------	-----

Electrical connection

Cable diameter D	3.3 mm
Cable length L	2 m
Conductor cross-section	0.24 mm <sup>2</sup>
Number of conductors	3
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

Environmental conditions

Ambient temperature	-30...60 °C
Contamination scale	1
IP rating	IP65

Functional safety

MTTF (40 °C)	595 a
--------------	-------

Interface

Switching output	PNP normally open (NO)
------------------	------------------------

Material

Cover material	PTFE
Housing material	PTFE
Material jacket	PTFE
Material sensing surface	PTFE

Mechanical data

Dimension	Ø 12 x 63 mm
Installation	non-flush
Size	M12x1
Thread (A)	M12x1
Tightening torque	0.5 Nm

Range/Distance

Hysteresis H max. (% of Sr)	15.0 %
Measuring range	1...6 mm
Rated operating distance Sn	6 mm
Repeat accuracy max. (% of Sr)	2.0 %
Temperature drift max. (% of Sr)	15 %

Remarks

The potentiometer does not have a fixed stop, but can be turned endlessly without destroying anything.  
If no change in the switching signal is detected, the potentiometer should be turned forwards or backwards until a signal change occurs at the output.  
For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Wiring Diagrams (Schematic)

