



1) Sensing surface, 2) Housing, 3) Cover, 4) Potentiometer, 5) LED Power, 6) LED function indicator



#### Basic features

Approval/Conformity	CE UKCA cULus WEEE
Basic standard	IEC 60947-5-2
Scope of delivery	Nut (2x)
Sensitivity	Switching distance adjustable
Series	M30
Trademark	Global

#### Display/Operation

Function indicator	yes
Power indicator	yes

#### Electrical connection

Cable diameter D	4.60 mm
Cable length L	2 m
Conductor cross-section	0.34 mm <sup>2</sup>
Number of conductors	3
Polarity reversal protected	yes
Protection against device mix-ups	no
Short-circuit protection	yes

#### Electrical data

No-load current I <sub>0</sub> max. at U <sub>e</sub>	20 mA
Operating voltage U <sub>b</sub>	10...30 VDC
Protection class	II
Rated insulation voltage U <sub>i</sub>	75 V DC
Rated operating current I <sub>e</sub>	100 mA
Rated operating voltage U <sub>e</sub> DC	24 V
Ready delay t <sub>v</sub> max.	300 ms
Ripple max. (% of U <sub>e</sub> )	10 %
Switching frequency	100 Hz
Utilization category	DC -13
Voltage drop static max.	1.5 V

#### Environmental conditions

Ambient temperature	-25...85 °C
Contamination scale	1
IP rating	IP67

#### Functional safety

MTTF (40 °C)	343 a
--------------	-------

#### Interface

Switching output	PNP normally closed (NC)
------------------	--------------------------

Capacitive Sensors  
BCS M30BBI1-POC15D-EP02  
Order Code: BCS00NN

**BALLUFF**

Material

Cover material	PBT
	PA
Housing material	PBT
Material jacket	PUR
Material sensing surface	PBT

Range/Distance

Hysteresis H max. (% of Sr)	15.0 %
Measuring range	2...15 mm
Rated operating distance Sn	15 mm
Repeat accuracy max. (% of Sr)	2.0 %
Temperature drift max. (% of Sr)	20 % [-5...55 °C]

Mechanical data

Dimension	Ø 30 x 66.5 mm
Installation	for flush mounting
Size	M30x1.5
Thread (A)	M30x1.5
Tightening torque	6 Nm

Remarks

The potentiometer does not have a fixed stop, but can be turned endlessly without destroying anything.  
If no change in the switching signal is detected, the potentiometer should be turned forwards or backwards until a signal change occurs at the output.  
For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Wiring Diagrams (Schematic)

