



### Basic features

|                     |                    |
|---------------------|--------------------|
| Approval/Conformity | CE<br>UKCA<br>WEEE |
| Basic standard      | IEC 60947-5-2      |

### Display/Operation

|                    |     |
|--------------------|-----|
| Function indicator | yes |
| Power indicator    | yes |

### Electrical connection

|                                   |     |
|-----------------------------------|-----|
| Polarity reversal protected       | yes |
| Protection against device mix-ups | yes |
| Short-circuit protection          | yes |

### Electrical data

|                                      |               |
|--------------------------------------|---------------|
| Load capacitance max. at $U_e$       | 1 $\mu$ F     |
| Min. operating current $I_m$         | 0 mA          |
| No-load current $I_o$ max., damped   | 20 mA         |
| No-load current $I_o$ max., undamped | 10 mA         |
| Operating voltage $U_b$              | 10...30 VDC   |
| Output resistance $R_a$              | 33.0 kOhm + D |
| Protection class                     | II            |
| Rated insulation voltage $U_i$       | 250 V AC      |
| Rated operating current $I_e$        | 200 mA        |
| Rated operating voltage $U_e$ DC     | 24 V          |
| Rated short circuit current          | 100 A         |
| Ready delay $t_v$ max.               | 30 ms         |
| Residual current $I_r$ max.          | 80 $\mu$ A    |
| Ripple max. (% of $U_e$ )            | 15 %          |
| Switching frequency                  | 50 Hz         |
| Utilization category                 | DC -13        |
| Voltage drop static max.             | 3.5 V         |

## Environmental conditions

|                         |                                       |
|-------------------------|---------------------------------------|
| Ambient temperature     | -25...70 °C                           |
| Contamination scale     | 3                                     |
| EN 60068-2-27, Shock    | Half-sinus, 30 g <sub>n</sub> , 11 ms |
| EN 60068-2-6, Vibration | 55 Hz, amplitude 1 mm, 3x30 min       |
| IP rating               | IP67                                  |

## Functional safety

|              |       |
|--------------|-------|
| MTTF (40 °C) | 730 a |
|--------------|-------|

## Interface

|                            |                        |
|----------------------------|------------------------|
| Cable fitting, thread size | M20x1.5                |
| Switching output           | PNP normally open (NO) |

## Material

|                          |     |
|--------------------------|-----|
| Housing material         | PBT |
| Material sensing surface | PBT |

## Mechanical data

|                                  |                     |
|----------------------------------|---------------------|
| Connection cross-section         | 2.5 mm <sup>2</sup> |
| Dimension                        | 120 x 40 x 40 mm    |
| Installation                     | non-flush           |
| Size                             | 40x40               |
| Tightening torque                | 4...5 Nm (M20x1.5)  |
| Tightening torque clamping screw | 0.8 Nm              |

## Range/Distance

|                                  |        |
|----------------------------------|--------|
| Assured operating distance Sa    | 20 mm  |
|                                  | 32 mm  |
| Hysteresis H max. (% of Sr)      | 20.0 % |
| Rated operating distance Sn      | 25 mm  |
| Real switching distance sr       | 40 mm  |
|                                  | 25 mm  |
| Repeat accuracy max. (% of Sr)   | 5.0 %  |
| Temperature drift max. (% of Sr) | 10 %   |
| Tolerance Sr                     | ±10 %  |

## Remarks

The sensor is functional again after the overload has been eliminated.  
 Factory setting Sn = 25 mm (switch position 1), in housing cover selectable to Sn = 40 mm (switch position 0).  
 LED 1: Function  
 LED 2: Operating voltage  
 Meets the requirements of VW-AG.  
 For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

## Wiring Diagrams (Schematic)

