



## Basic features

|                     |   |
|---------------------|---|
| Additional features | Factor 1<br>Extended temperature range<br>weld-immune (magnetic field<br>100kA/m) |
| Approval/Conformity | CE<br>UKCA<br>cULus<br>WEEE   |
| Basic standard      | IEC 60947-5-2   |
| Scope of delivery   | No nuts or lockwashers  |

## Display/Operation

|                    |     |
|--------------------|-----|
| Function indicator | yes |
| Power indicator    | no  |

## Electrical connection

|                                   |                            |
|-----------------------------------|----------------------------|
| Connection                        | M12x1-Male, 3-pin, A-coded |
| Electrical version                | 3-wire                     |
| Polarity reversal protected       | yes                        |
| Protection against device mix-ups | yes                        |
| Short-circuit protection          | yes                        |

## Electrical data

|   |                          |
|---|--------------------------|
| Load capacitance max. at Ue                   | 1 µF                     |
| Magnetic field strength, interference field   | 100 kA/m                 |
| Min. operating current I <sub>m</sub>         | 0 mA                     |
| No-load current I <sub>o</sub> max., damped   | 15 mA                    |
| No-load current I <sub>o</sub> max., undamped | 5 mA                     |
| Operating voltage U <sub>b</sub>              | 10...30 VDC              |
| Output resistance R <sub>a</sub>              | 33.0 kΩ <sub>m</sub> + D |
| Protection class                              | II                       |
| Rated insulation voltage U <sub>i</sub>       | 250 V AC                 |
| Rated operating current I <sub>e</sub>        | 200 mA                   |
| Rated operating voltage U <sub>e</sub> DC     | 24 V                     |
| Rated short circuit current                   | 100 A                    |
| Ready delay t <sub>v</sub> max.               | 2 ms                     |
| Ripple max. (% of U <sub>e</sub> )            | 15 %                     |
| Switching frequency                           | 800 Hz                   |
| Utilization category                          | DC -13                   |
| Voltage drop static max.                      | 2 V                      |

## Environmental conditions

|                         |                                       |
|-------------------------|---------------------------------------|
| Ambient temperature     | -25...85 °C                           |
| Contamination scale     | 3                                     |
| EN 60068-2-27, Shock    | Half-sinus, 30 g <sub>n</sub> , 11 ms |
| EN 60068-2-6, Vibration | 55 Hz, amplitude 1 mm, 3x30 min       |
| IP rating               | IP67, according to BWN Pr 20          |
| Magnetic field immune   | magnetic field immune (AC/DC)         |

## Functional safety

|              |         |
|--------------|---------|
| MTTF (40 °C) | 400.5 a |
|--------------|---------|

## Interface

Switching output PNP normally open (NO)

## Material

Housing material Brass, Nickel-free coated  
 Material sensing surface PBT

## Mechanical data

Dimension  $\varnothing 18 \times 66$  mm  
 Installation non-flush  
 Mounting length 40.5 mm  
 Size M18x1  
 Tightening torque 25 Nm

## Range/Distance

Assured operating distance Sa 6.4 mm  
 Hysteresis H max. (% of Sr) 15.0 %  
 Rated operating distance Sn 8 mm  
 Real switching distance sr 8 mm  
 Repeat accuracy max. (% of Sr) 5.0 %  
 Switching distance marking ■  
 Temperature drift max. (% of Sr) 10 %  
 Tolerance Sr 10 %

## Remarks

The sensor is functional again after the overload has been eliminated.  
 For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

## Connector Drawings



## Wiring Diagrams (Schematic)

