



Basic features

Additional features	Factor 1 Extended temperature range weld-immune (magnetic field 100kA/m)
Approval/Conformity	CE UKCA cULus WEEE
Basic standard	IEC 60947-5-2
Scope of delivery	No nuts or lockwashers

Display/Operation

Function indicator	yes
Power indicator	no

Electrical connection

Connection	M12x1-Male, 3-pin, A-coded
Electrical version	3-wire
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

Electrical data

Load capacitance max. at Ue	1 µF
Magnetic field strength, interference field	100 kA/m
Min. operating current Im	0 mA
No-load current Io max., damped	15 mA
No-load current Io max., undamped	5 mA
Operating voltage Ub	10...30 VDC
Output resistance Ra	33.0 kOhm + D
Protection class	II
Rated insulation voltage Ui	250 V AC
Rated operating current Ie	200 mA
Rated operating voltage Ue DC	24 V
Rated short circuit current	100 A
Ready delay tv max.	2 ms
Ripple max. (% of Ue)	15 %
Switching frequency	800 Hz
Utilization category	DC -13
Voltage drop static max.	2 V

Environmental conditions

Ambient temperature	-40...85 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 gn, 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP67, according to BWN Pr 20
Magnetic field immune	magnetic field immune (AC/DC)

Functional safety

MTTF (40 °C)	400.5 a
--------------	---------

Inductive Sensors
BES M18MI-PSC50A-S04G
Order Code: BES05WM

BALLUFF

Interface

Switching output PNP normally open (NO)

Material

Housing material Brass, Nickel-free coated
Material sensing surface PBT

Mechanical data

Dimension Ø 18 x 66 mm
Installation for flush mounting
Mounting length 50.5 mm
Size M18x1
Tightening torque 15 Nm

Range/Distance

Assured operating distance Sa 4 mm
Hysteresis H max. (% of Sr) 15.0 %
Rated operating distance Sn 5 mm
Real switching distance sr 5 mm
Repeat accuracy max. (% of Sr) 5.0 %
Switching distance marking ■
Temperature drift max. (% of Sr) 10 %
Tolerance Sr 10 %

Remarks

The sensor is functional again after the overload has been eliminated.
For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams (Schematic)

