



1) O-Ring with thrust ring, 2) Recess for circlip



Basic features

Approval/Conformity	CE UKCA cULus WEEE
Base type deviation	Recess for circlip Housing length
Basic standard	IEC 60947-5-2

Display/Operation

Function indicator	no
Power indicator	no

Electrical connection

Connection	M12x1-Male, 4-pin, A-coded
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

Electrical data

Load capacitance max. at Ue	1 µF
Min. operating current Im	0 mA
No-load current Io max., damped	15 mA
No-load current Io max., undamped	15 mA
Operating voltage Ub	12...36 VDC
Output resistance Ra	33.0 kOhm + D
Rated insulation voltage Ui	75 V DC
Rated operating current Ie	200 mA
Rated operating voltage Ue DC	24 V
Rated short circuit current	100 A
Ready delay tv max.	100 ms
Residual current Ir max.	10 µA
Ripple max. (% of Ue)	15 %
Switching frequency	1500 Hz
Utilization category	DC -13
Voltage drop static max.	2.5 V

Environmental conditions

Ambient temperature	-25...85 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 gn, 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP67

Functional safety

MTTF (40 °C)	155 a
--------------	-------

Interface

Switching output	PNP normally open/normally closed (NO/NC)
-------------------------	---

Material

Housing material	1.4104 stainless steel
Material sensing surface	Ceramic
Support ring material	PTFE

Mechanical data

Dimension	Ø 12 x 69 mm
Installation	for flush mounting
Mounting length	12.00 mm
Mounting part	M12x1
Pressure rating max.	500 bar
Pressure rating, note	oil pressure rated
Sealing ring, size	6.75 x 1.78 mm
Size	M12x1
Tightening torque	15 Nm ±10 %

Range/Distance

Assured operating distance Sa	1.2 mm
Hysteresis H max. (% of Sr)	15.0 %
Rated operating distance Sn	1.5 mm
Real switching distance sr	1.5 mm
Repeat accuracy max. (% of Sr)	5.0 %
Temperature drift max. (% of Sr)	10 %
Tolerance Sr	±10 %

Remarks

Installation Instructions 614804

The sensor is functional again after the overload has been eliminated.

For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams (Schematic)

