



FD-MZ10AYK

Main Unit, Landscape, 10 L/min, NPN



*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

Specifications

Model	FD-MZ10AYK*1	
Type	Horizontal	
Shape	Built-in amplifier	
Rated flow range	0.14 - 2.60 G/min (0.50 - 10 L/min)*1	
Possible display range	0.14 - 6.35 G/min (0.50 - 30 L/min)*2	
Possible ranges to set	0 - 6.35 G/min (0 - 30 L/min)	
Connection port	NPT3/8 (10 A)	
Detectable fluids	Water or non-corrosive liquid	
Conductivity of detection fluids	5 μ S/cm or higher	
Detection fluid temperature	0 to +85°C 32 to 185 °F (No freezing)	
Pressure loss	Max. 1.45 PSI (0.01 MPa)	
Display method	Dual row display with 4-digit, 7 segment LED, bar display (2 colors), output indicators, flow indicator	
Display resolution	0.01/0.1 (G/min, L/min) selectable	
Repeatability	0.5 s : \pm 5% of F.S., 1 s : \pm 3.5% of F.S., 2.5 s : \pm 2.5% of F.S., 5 s : \pm 1.6% of F.S., 10 s : \pm 1% of F.S., 30 s : \pm 0.8% of F.S., 60 s : \pm 0.6% of F.S.*3	
Hysteresis	Variable	
Response time (chatter prevention feature)	0.5 s/1 s/2.5 s/5 s/10 s/30 s/60 s variable	
Accumulated flow unit	0.01/0.1/1/10/100 (G, L) selectable	
Integration data storage cycle	Save to memory every 10 seconds	
Memory backup	EEPROM (Data storage length : 10 years or longer, Data read/write frequency : 1 million times or more)	
Analog output	4-20 mA, max. load resistance 260 Ω Analog output range can be set to any value	
Integration reset/bank switch input/flow zero function input	Input time : 20 ms or greater, Select either the accumulation output or the accumulation pulse by setting the mode	
Power consumption (Current consumption)	Normal : 1700 mW (70 mA), Power save : 1000 mW (40 mA)	
Rating	Power voltage	24 VDC, Ripple (P-P) 10 % or less, Class 2
Environmental resistance	Enclosure rating	IP65
	Pressure resistance	290 PSI (2.0 MPa)
	Applied pressure range	Max. 145 PSI (1.0 MPa)
	Ambient temperature	0 to +50 °C 32 to 122 °F (No freezing)
	Relative humidity	35 to 85 % RH (No condensation)
	Vibration resistance	10 to 55 Hz, Double amplitude 1.5 mm 0.06" , 2 hours in each of the X, Y, and Z directions
Material	Liquid end materials	Bore : SCS13, Measurement pipe : PPS, O ring : fluoro-rubber (FKM)
	Other materials	Plastic case areas : PPS, Metal case areas : SUS430, Cable : PVC
Accessory	Instruction Manual, Connector cable (2.7 m 106.3")	

Weight	Approx. 865 g
--------	---------------

*1 The rated flow range indicates recommended operating range.

*2 Can be used within the display range as well as within the rated flow range.

*3 The repeatability for FD-MZ10ATK (P)/YK (P) in the range of 5.20 to 7.50 G/min (20 to 30 L/min) is the double of the value listed in the table. The repeatability is the error of the detection point when fluids flow repeatedly under the same conditions.