



FU-88

Fiber Unit Thrubeam type

*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

Specifications

Model		FU-88*1
Optical axis diameter (Standard target to be detected)		ø1.5 mm0.059"
Heat resistant temperature		180°C 356°F*2*3
Fibre unit length		2 m78.74" free-cut
Fibre unit diameter		ø2.2
Minimum bend radius		R35 mm1.378"
Minimum detectable object		Object with a diameter of 0.005 mm0.0002"*4
Environmental resistance	Ambient temperature	-60 to +180 °C -76 to 356 °F
Weight		Approx. 36 g

*1 For details on the detecting distance, see the fiber amplifier catalog.
*2 When this product is used in an environment with a consistently high temperature, we recommend a usage temperature of 150°C 302°F or less.
*3 Use in a dry state. Also, when using the heat resistant type, make a selection with ample room for the ambient temperature.
*4 The minimum detectable object is the value when the detecting distance and sensitivity have been set to their optimal state.

* Download CAD file or product manual for larger image/text and more detail.

Technical drawing of a fiber optic cable assembly. The drawing shows a side view of the cable with a bend and a cross-sectional view of the core fiber. Dimensions and specifications are provided:

- Core fiber:** $\phi 1.5$ Core fiber
- Outer diameter:** $\phi 2.9$ (at the connector), $\phi 2.2$ (at the bend)
- Material:** SUS304
- Thread:** M4 P=0.7
- Across-flats:** 7, Thickness: 2
- Dimensions:** 1, 15, 2000