



# GV-H1000

Sensor Head Ultra-long-distance Type



\*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

## Specifications

Model			GV-H1000
Type			Ultra long-range
Light source			Visible semiconductor laser, Wavelength: 655 nm
Laser class	FDA (CDRH) Part 1040.10		Class 2 (560 μW)
	IEC 60825-1		
	JIS C6802		
Detection distance (Amplifier display )			200 to 1000 mm 7.87" to 39.37" (800 to 0)*1)
Possible display range			810 to -175
Standard detection deviation			20 mm 0.79" (Detection distance 200 to 800 mm 7.87" to 31.5") 30 mm 1.18" (Detection distance 800 to 1000 mm 31.5" to 39.37")
Spot diameter			Approx. ø1.8 mm ø0.07" (Detection distance 1000 mm 39.37")
Operation status indicators			Control output: Red LED/Laser radiation emission indicator: Green LED/1 spot indicator: Green LED
Environmental resistance	Enclosure rating		IP67
	Operating ambientluminance	Incandescent lamp	5000lx
		Sunlight	10000lx*2
	Ambient temperature		-10 to +50 °C 14 to 122 °F (No freezing)
	Relative humidity		35 to 85 % RH (No condensation)
Vibration resistance		10 to 55 Hz, Double amplitude 1.5 mm 0.06", 2 hours in each of the X, Y, and Z axis	
Material			Housing material: PBT, Display: Polyarylate, Metal: SUS304, Lens cover: Glass, Cable: PVC
Weight			Approx. 210 g*3

\*1 General guideline for amplifier display values relative to detection distance (when distance display mode is set to normal).  
\*2 Incandescent lamp: 5000 lux, Sunlight: 3000 lux for GV-H1000 (When the response time is set to 10 ms or faster)  
\*3 Including 2 m 6.6' connector cable (3 m 9.8' cable for GV-H1000)

Dimensions

\* Download CAD file or product manual for larger image/text and more detail.

GV-H1000/GV-H1000L

