

Dimension M 18 x 1

M 18 x 1

M 18 x 1

M 18 x 1


Flush mountable		Flush mountable		Flush mountable	
5 mm		5 mm		5 mm	
1...8 mm		1...8 mm		1...8 mm	
Type code	Art. No.	Type code	Art. No.	Type code	Art. No.
KAS-70-A13-A-M18-PPO-Z02-1-NL	KA 0637				
KAS-70-A13-S-M18-PPO-Z02-1-NL	KA 0648	KAS-70-A13-S-M18-PPO-Y3-1-NL	KA 0609		
KAS-80-A13-A-M18-PPO-Z02-1-NL	KA 0680	KAS-80-A13-A-M18-PPO-Y3-1-NL	KA 0607		
KAS-80-A13-S-M18-PPO-Z02-1-NL	KA 0717				
				KAS-90-A13-S-M18-PPO-Z02-1-NL	KA0634
				KAS-90-A13-Ö-M18-PPO-Z02-1-NL	KA0724
CE, RoHS, UL-CSA		CE, RoHS, UL-CSA		CE, RoHS, UL-CSA	
12...30 V DC		12...30 V DC		20...250 V AC / DC	
200 mA / 2 x 200 mA		200 mA / 2 x 200 mA		250 mA	
< 15 mA		< 15 mA		< 2,5 mA	
-		-		5 mA	
200 Hz		200 Hz		25 Hz	
-25...+70 °C		-25...+70 °C		-25...+70 °C (ETL = +60 °C)	
Yes		Yes		Yes	
Yes		Yes		Yes	
IEC 60947-5-2		IEC 60947-5-2		IEC 60947-5-2	
IP 67*		IP 67*		IP 67*	
2 m cable, PUR, 3 x 0.34 mm ² PVC, 4 x 0.34 mm ² for antivalent		Flange connector M 12 x 1		2 m cable, PUR 2 x 0.34 mm ²	
PA / PPO		PA / PPO		PA / PPO	
PA / PPO		PA / PPO		PA / PPO	
PA / PPO		-		PA / PPO	

