

Dimension M 12 x 1

| M 12 x 1 | | M 12 x 1 | | M 12 x 1 | |
|---|----------|---|----------|---|----------|
|  | |  | |  | |
| Flush mountable | | Non-flush mountable | | Non-flush mountable | |
| 2 mm | | 4 mm | | 4 mm | |
| 0.5...5 mm | | 1...8 mm | | 1...8 mm | |
| Type code | Art. No. | Type code | Art. No. | Type code | Art. No. |
| KAS-70-A12-A-M12-PPO/VAb-Y5-1-NL | KA 0710 | KAS-70-A22-A-M12-PTFE/VAb-Z02-1-NL | KA 0711 | KAS-70-A22-A-M12-PTFE/VAb-Y5-1-NL | KA 0715 |
| | | KAS-70-A22-S-M12-PTFE/VAb-Z02-1-NL | KA 0712 | | |
| KAS-80-A12-A-M12-PPO/VAb-Y5-1-NL | KA 0670 | KAS-80-A22-A-M12-PTFE/VAb-Z02-1-NL | KA 0713 | KAS-80-A22-A-M12-PTFE/VAb-Y5-1-NL | KA 0716 |
| | | KAS-80-A22-S-M12-PTFE/VAb-Z02-1-NL | KA 0714 | | |
| | | | | | |
| | | | | | |
| CE, RoHS, UL-CSA | | CE, RoHS, UL-CSA | | CE, RoHS, UL-CSA | |
| 12...30 V DC | | 12...30 V DC | | 12...30 V DC | |
| 2 x 200 mA | | 200 mA / 2 x 200 mA | | 2 x 200 mA | |
| < 15 mA | | < 15 mA | | < 15 mA | |
| - | | - | | - | |
| 300 Hz | | 50 Hz | | 50 Hz | |
| -25...+70 °C | | -25...+70 °C | | -25...+70 °C | |
| Yes | | Yes | | Yes | |
| Yes | | Yes | | Yes | |
| IEC 60947-5-2 | | IEC 60947-5-2 | | IEC 60947-5-2 | |
| IP 67* | | IP 67* | | IP 67* | |
| Flange connector M 12 x 1 | | 2 m cable, PUR, 3 x 0.14 mm ² 4 x 0.14 mm ² for antivalent | | Flange connector M 12 x 1 | |
| VA No. 1.4305 | | VA No. 1.4305 | | VA No. 1.4305 | |
| PA / PPO | | PTFE (FDA 21 CFR 177.1550) | | PTFE (FDA 21 CFR 177.1550) | |
| - | | PA / PPO | | - | |

