



# KV-E4R

4 Relay Outputs



\*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

 This model has been discontinued.  
Compliance with the certification standard is ensured as of the time of shipment from our company.

Contact Us: 1-888-539-3623

Recommended Replaceable Products: [Expansion output unit, output 8 points, relay output, screw terminal block - KV-N8ER](#)

## Specifications

|                                   |                            |                                                                                           |
|-----------------------------------|----------------------------|-------------------------------------------------------------------------------------------|
| Model                             |                            | KV-E4R                                                                                    |
| Number of outputs                 |                            | 4                                                                                         |
| Output                            |                            | Relay                                                                                     |
| Rated load voltage                |                            | 250 VAC/30 VDC, 2 A (Inductive load), 4 A (Resistive load)                                |
| Rated output current              |                            | 2 A/output (inductive load), 4 A/output (resistive load), 4 A/common                      |
| Leakage current (at OFF)          |                            | —                                                                                         |
| Residual voltage (at ON)          |                            |                                                                                           |
| Startup operation time (OFF → ON) |                            | 10ms or less                                                                              |
| Startup operation time (ON → OFF) |                            |                                                                                           |
| ON resistance                     |                            | 50 mΩ or less                                                                             |
| Relay life span                   |                            | Electrical: 100,000 times or more (20 times/minute), mechanical: 20,000,000 times or more |
| Relay replacement                 |                            | Not possible                                                                              |
| General specifications            | Weight                     | Approx 100g                                                                               |
| Output specifications             | Common output              | 4/common                                                                                  |
|                                   | External connection method | Terminal block                                                                            |

# Dimensions

\* Download CAD file or product manual for larger image/text and more detail.

Kv-e4

