



KV-E4XR

4 Inputs and 4 Relay Outputs



*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

! This model has been discontinued. Compliance with the certification standard is ensured as of the time of shipment from our company.

Contact Us: 1-888-539-3623

Recommended Replaceable Products: [Expansion I/O unit, 16-point type, Screw Terminal Block, Input 8 points, relay output 8 points - KV-N8EXR](#)

Specifications

Model		KV-E4XR	
Number of inputs		4	
Minimum ON voltage		19V	
Maximum OFF current		2mA	
Input time constant (switchable between 2 levels by using special auxiliary relays 2609 to 2612)		10 ms \pm 20%, 10 μ s \pm 20% for both rising (OFF to ON) and falling (ON to OFF) edges	
Number of outputs		4	
Output		Relay	
Rated load voltage		250 VAC/30 VDC, 2 A (Inductive load), 4 A (Resistive load)	
Rated output current		2 A/output (inductive load), 4 A/output (resistive load), 4 A/common	
Leakage current (at OFF)		—	
Residual voltage (at ON)			
Startup operation time (OFF \rightarrow ON)		10ms or less	
Startup operation time (ON \rightarrow OFF)			
ON resistance		50 m Ω or less	
Relay life span		Electrical: 100,000 times or more (20 times/minute), mechanical: 20,000,000 times or more	
Relay replacement		Not possible	
General specifications	Weight		Approx 120g
Input specifications	24 V mode	Input maximum rating	26.4 VDC
		Input voltage	24 VDC, 5.3 mA
		Input impedance	4.3 k Ω
	Common input	4/common	
Output specifications	Common output		
	External connection method		Terminal block

Dimensions

* Download CAD file or product manual for larger image/text and more detail.

Kv-e8

