



KV-NC20L

Serial adapter RS-232C/422A/485



*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

Specifications

Model		KV-NC20L	
Transmission specifications	Electrical termination (Terminator)	Set with the switch on the front panel of the main unit	
	Baud rate	1200, 2400, 4800, 9600, 19200, 38400, 57600, 115200 bps	
	Transmission method	Port1 : Full duplex Port2 : Full duplex, Half duplex	
	Data format	Start bit	1 bit
		Data bits	7 bits, 8 bits
		Stop bits	1 bits, 2 bits
	Error detection	Parity	Even, odd, none
RS/CS flow control		Port1 : Enabled, disabled	
Interface	Communication standard	Port 1 : RS-232C Port2 : RS-232C, RS-422A/RS-485 (4-wire), RS-485 (2-wire)	
	Connection	Port 1 : D-sub 9-pin Port 2 : European terminal block	
Transmission specifications	Transmission distance	Port1 : 15 m 49.2' Port2 : 15 m 49.2' , Extendable up to 1200 m 3937.0'	
	Number of transmission units	Port1 : 1 Port2 : 1, 32	
Indication		SD (orange), RD (orange)	
Weight		Approx. 110 g	

Dimensions

* Download CAD file or product manual for larger image/text and more detail.

KV-NC20L

