

# XCKJ167H29C

Limit switch, XC Standard, XCKJ, steel roller plunger reinforced, 1NC+1 NO, snap, M20



## Main

|                               |   |
|-------------------------------|---|
| Range of product              | Telemecanique Limit switches XC Standard                                  |
| Series name                   | Standard format   |
| Product or component type     | Limit switch  |
| Device short name             | XCKJ  |
| Sensor design                 | Form C conforming to CENELEC EN 50041                                     |
| Body type                     | Fixed   |
| Head type                     | Plunger head  |
| Material                      | Metal   |
| Body material                 | Zamak   |
| Head material                 | Zamak   |
| Fixing mode                   | By the body   |
| Movement of operating head    | Linear  |
| Type of operator              | Spring return roller plunger metal reinforced                             |
| Type of approach              | Lateral approach, 2 directions  |
| Cable entry                   | 1 entry tapped for M20 x 1.5 cable gland, cable outer diameter: 7...13 mm |
| Number of poles               | 2   |
| Contacts type and composition | 1 NC + 1 NO   |
| Contact operation             | Snap action   |

## Complementary

|  |   |
|--|---|
| Switch actuation                             | By 30° cam  |
| Electrical connection                        | Screw-clamp terminals, clamping capacity: 1 x 0.34...2 x 1.5 mm <sup>2</sup>  |
| Contacts insulation form                     | Zb  |
| Number of steps                              | 1   |
| Positive opening                             | With  |
| Positive opening minimum force               | 40 N  |
| Minimum force for tripping                   | 16 N  |
| Maximum actuation speed                      | 1 m/s   |
| [Ie] rated operational current               | 3 A at 240 V, AC-15, A300 conforming to EN/IEC 60947-5-1 appendix A<br>0.27 A at 250 V, DC-13, Q300 conforming to EN/IEC 60947-5-1 appendix A   |
| [Ithe] conventional enclosed thermal current | 10 A  |
| [Ui] rated insulation voltage                | 300 V conforming to UL 508<br>500 V (pollution degree 3) conforming to IEC 60947-1<br>300 V conforming to CSA C22.2 No 14   |
| Maximum resistance across terminals          | 25 MOhm conforming to IEC 60255-7 category 3  |
| [Uimp] rated impulse withstand voltage       | 6 kV conforming to IEC 60664<br>6 kV conforming to IEC 60947-1  |
| Short-circuit protection                     | 10 A cartridge fuse, type gG  |
| Electrical durability                        | 5000000 Cycles, DC-13, inductive load type, 120 V, 4 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 Cycles, DC-13, inductive load type, 24 V, 10 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13, inductive load type, 48 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Mechanical durability                        | 25000000 cycles   |
| Width  | 40 mm   |
| Height                                       | 77 mm   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TWSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                               |                        |
|-------------------------------|------------------------|
| Depth                         | 44 mm                  |
| Net weight                    | 0.455 kg               |
| Terminals description ISO n°1 | (13-14)NO<br>(21-22)NC |

## Environment

|                                       |   |
|---------------------------------------|---|
| Shock resistance                      | 50 gn for 11 ms conforming to IEC 60068-2-27  |
| Vibration resistance                  | 25 gn (f= 10...500 Hz) conforming to IEC 60068-2-6  |
| IP degree of protection               | IP66 conforming to IEC 60529  |
| IK degree of protection               | IK07 conforming to EN 50102   |
| Overvoltage category                  | Class I conforming to IEC 61140<br>Class I conforming to NF C 20-030  |
| Ambient air temperature for operation | -25...70 °C   |
| Ambient air temperature for storage   | -40...70 °C   |
| Protective treatment                  | TH  |
| Product certifications                | CCC   |
| Standards                             | EN 60204-1<br>IEC 60204-1<br>IEC 60947-5-1<br>EN 60947-5-1<br>CSA C22.2 No 14<br>CENELEC EN 50041<br>UL 508 |

## Packing Units

|                              |            |
|------------------------------|------------|
| Unit Type of Package 1       | PCE        |
| Number of Units in Package 1 | 1          |
| Package 1 Height             | 4.2 cm     |
| Package 1 Width              | 6.862 cm   |
| Package 1 Length             | 12.817 cm  |
| Package 1 Weight             | 440.0 g    |
| Unit Type of Package 2       | S02        |
| Number of Units in Package 2 | 30         |
| Package 2 Height             | 15.0 cm    |
| Package 2 Width              | 30.0 cm    |
| Package 2 Length             | 40.0 cm    |
| Package 2 Weight             | 13.671 kg  |
| Unit Type of Package 3       | PAL        |
| Number of Units in Package 3 | 480        |
| Package 3 Height             | 75.0 cm    |
| Package 3 Width              | 60.0 cm    |
| Package 3 Length             | 80.0 cm    |
| Package 3 Weight             | 231.842 kg |

## Offer Sustainability

|  |   |
|--|---|
| Sustainable offer status                   | Green Premium product   |
| Circularity Profile                        | No need of specific recycling operations  |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>  |